

# **Rivulis Super XL**: Continuous stream, slow rotating rotor sprinkler

Ideal for: Nurseries, frost protection or any application where you need a medium sized sprinkler with excellent uniformity



www.rivulis.com

## **Product Information**

Technical	Data						
Operating pressure range	2.5 - 3.5 bar						
Drive	Slow rotation silicone drive						
Connection	3/8" and 1/2" Male Threaded models available						
Pressure (for flow rate calculation)	2.5 bar						
Filtration requirements							
All Flow Rates:	250 micron / 60 mesh						

#### Rivulis Super XL $\cdot$ Maximum Recommended Number of Sprinklers on Laterals

Nominal Flow Rate	Nozzle	Hose Size	Spacir	ng Betwee	en Sprinkle	ers (m)
lph	Color	mm	6	7	8	9
191	Violet		32	31	29	28
235	Yellow	10/266	28	27	25	24
290	Brown	40 / 36.6	25	23	22	21
341	Orange		22	21	20	19



## **Performance Information**

Nozzle			Wet	ting	Application Rate (mm/h)**													
Color &	Pressure Rate		Diameter (m)*		Spacing (mxm) - Rectangular Layout ***													
Size			Black	Rotor	бхб	6x7	6x8	6x9	6x10	7x7	7x8	7x9	7x10	8x8	8x9	8x10	9x9	9x10
mm	bar	lph	Black Cover	Green Cover		Number of sprays									<ul> <li>2.3</li> <li>2.6</li> <li>2.9</li> <li>3.2</li> <li>3.5</li> <li>3.8</li> </ul>			
Violet 1.8	3	209	14.5	-	5.8	5	4.4	3.9	3.5	4.3	3.7	3.3	3	3.3	2.9	2.6	2.6	2.3
Yellow	2.5	235	15.0	-	6.5	5.6	4.9	4.4	3.9	4.8	4.2	3.7	3.4	3.7	3.3	2.9	2.9	2.6 2.9 3.2
2.0	3	258	15.0	-	7.2	6.1	5.4	4.8	4.3	5.3	4.6	4.1	3.7	4	3.6	3.2	3.2	2.9
Brown	2.5	290	-	16.0	8.1	6.9	6	5.4	4.8	5.9	5.2	4.6	4.1	4.5	4	3.6	3.6	3.2
2.2	3	315	-	- 16.0 8.8 7.5 6.6	5.8	5.3	6.4	5.6	5	4.5	4.9	4.4	3.9	3.9	3.5			
Orange	2.5	341	-	16.5	9.5	8.1	7.1	6.3	5.7	7	6.1	5.4	4.9	5.3	4.7	4.3	4.3 4.2 3.8	
2.4	3	373	-	16.5	10.4	8.9	7.8	6.9	6.2	7.6	6.7	5.9	5.3	5.8	5.2	4.7	4.6	4.1

\* At 75 cm above ground level

\*\* Performance data are obtained under ideal test conditions and may be adversely affected by wind, hydraulic conditions, and other factors.

\*\*\* 8x10, 9x9, 9x10 - Recommended for undertree irrigation

#### **Rivulis Super XL Flow Rate / Pressure**

	Color	Color Code (nozzle) / Flow Rate (lph)											
Pressure (bar)	Violet	Yellow	Brown	Orange									
2.00	171	212	259	305									
2.50	191	235	290	341									
3.00	209	258	315	373									
3.50	226	278	341	401									

### **Product List**

#### Rivulis Super XL Sprinkler

nivans saper AE	Sprinkie								
Product Description	Inlet connection	Flow Rate (lph at 2.5 bar)	Spray Diameter (m) at 2.5 bar	Rotor	Nozzle Color	Quantity (bag)	Quantity (box)	Product Number	
Super XL Sprinkler I 191 lph I 3/8" Thread		191.0	14.5	Blue	Purple	250	1000	101003649	
Super XL Sprinkler I 235 lph I 3/8" Thread	3/8" Male Thread	235.0	15.0	Blue	Yellow	250	1000	101003653	
Super XL Sprinkler I 290 lph I 3/8" Thread		290.0	16.0	Green	Brown	250	1000	101003650	6
Super XL Sprinkler I 341 lph I 3/8" Thread		341.0	16.5	Green	Orange	250	1000	101003651	
Super XL Sprinkler I 191 lph I 1/2" Thread		191.0	14.5	Blue	Purple	250	1000	101003655	
Super XL Sprinkler I 235 lph I 1/2" Thread	1/2" Male	235.0	15.0	Blue	Yellow	250	1000	101003656	
Super XL Sprinkler I 290 lph I 1/2" Thread	Thread	290.0	16.0	Green	Brown	250	1000	101003657	
Super XL Sprinkler I 341 lph I 1/2" Thread		341.0	16.5	Green	Orange	250	1000	101003658	



Case study outcomes are for information purposes only and actual results may vary. This literature has been compiled for worldwide circulation and the descriptions, photos, and information are for general purpose use only. Please consult with an irrigation specialist and technical specifications for proper use of Rivulis products. Because some products are not available in all regions, please contact your local dealer for details. Rivulis reserves the right to change specifications and the design of all products without notice. Every effort has been used to ensure that product information, including data sheets, schematics, manuals and brochures are correct. However information should be verified before making any decisions based on this information.

