

MINING PRESSURE REGULATORS

MINING PRL & CMS



PRL063F3FC	6 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	R0.00
PRL103F3FC	10 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	R0.00
PRL123F3FC	12 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	R0.00
PRL153F3FC	15 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	
PRL203F3FC	20 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	
PRL253F3FC	25 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	
PRL303F3FC	30 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	
PRL353F3FC	35 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	
PRL403F3FC	40 psi, inlet 3/4" F NPT, outlet 3/4" F NPT	

The PRL (Pressure Regulator Low Flow) has two models available for either copper (CMS) or gold and silver mining installations requiring lower flows of 0.5 to 8.0 gpm (114 to 1817 L/hr).

Maintains a constant preset outlet pressure while handling varying inlet pressures

Inlet sizes: 3/4" NPT female, 3/4" female hose. Outlet sizes: 3/4" NPT female

Tamper-proof housing

Very low hysteresis and friction losses

100% water-tested for accuracy at Senninger's in-house facilities

No external metal parts for excellent corrosion resistance