WASTE WATER PRESSURE REGULATORS

PRU





PRU108F8F	10 psi, inlet 2" F NPT, outlet 2" F NPT	R0.00
PRU158F8F	15 psi, inlet 2" F NPT, outlet 2" F NPT	R0.00
PRU208F8F	20 psi, inlet 2" F NPT, outlet 2" F NPT	RO.00
PRU258F8F	25 psi, inlet 2" F NPT, outlet 2" F NPT	
PRU308F8F	30 psi, inlet 2" F NPT, outlet 2" F NPT	
PRU408F8F	40 psi, inlet 2" F NPT, outlet 2" F NPT	
PRU508F8F	50 psi, inlet 2" F NPT, outlet 2" F NPT	
PRU608F8F	60 psi, inlet 2" F NPT, outlet 2" F NPT	

20 to 100 gpm (4543 to 22713 L/hr) Flows:

Pressures: 10 to 60 psi (0.69 to 4.14 bar) based on model

The PRU (Pressure Regulator Ultra) was designed to handle higher flows of 20 to 100 gpm (4543 - 22713 L/hr). Its 2-inch inlet and outlet size make it an ideal option for accurate zone and individual sprinkler pressure control. Its compact size fits in a valve box.

100% pressure tested, to ensure quality and performance Very low hysteresis and friction loss

Large flow path resists plugging

Connections: 2" F NPT x 2" F NPT or 2" F BSPT x 2" F BSPT models available

Corrosion resistant

